



CABLE SPECIFICATION

Pages	CABLE SIZE	SIZE(in)	DIA (in)	B.S (lbs)	WEIGHT (lbs/kft)	ARMOR WIRES IN/OUT	WIRES B.S. (lbs) IN/OUT	STRETCH COEFFICIENT ft/Kft/Klbs	CDR RESIS OHMS/Kft	CAP Pf/Ft	MAX TEMP °F	MIN SHEAVE DIA (in)	MAX VOLT
10	1-P-185-12/12-G-7	3/16	0.185	4000	65	12/12	103/282	3.00	9.4	53	300	14	1000
11	1-T-185-12/12-G-7	3/16	0.185	4000	67	12/12	103/282	3.00	9.4	63	500	14	1000
12	1-P-224-12/18-G-19	7/32	0.224	5600	94	12/18	204/204	2.50	4.0	59	300	14	1200
13	1-T-224-12/18-G-19	7/32	0.224	5600	97	12/18	204/204	2.50	4.0	68	500	14	1200
14	1-A-224-12/18-G-19	7/32	0.224	5600	99	12/18	204/204	2.50	4.0	58	550	14	1200
15	1-Q-224-12/18-G-19	7/32	0.224	5600	99	12/18	204/204	2.50	4.0	58	600	14	1200
16	1-A-224-12/18-75-7	7/32	0.224	4800	96	12/18	186/186	2.90	6.7	43	500	14	1200
17	1-A-224-12/18-77-7	7/32	0.224	5200	97	12/18	196/196	3.10	6.7	43	500	14	1200
18	1-A-224-12/18-35N-7	7/32	0.224	5200	100	12/18	204/204	2.90	6.7	43	500	14	1200
19	1-P-224-15/15-G-19	7/32	0.224	5600	94	15/15	129/282	2.20	4.0	60	300	14	1200
20	1-T-224-15/15-G-19	7/32	0.224	5600	97	15/15	129/282	2.20	4.0	69	500	14	1200
21	1-A-224-15/15-G-19	7/32	0.224	5600	99	15/15	129/282	2.20	4.0	58	550	14	1200
22	1-Q-224-15/15-G-19	7/32	0.224	5600	99	15/15	129/282	2.20	4.0	58	600	14	1200
23	1-A-224-15/15-75-7	7/32	0.224	4800	96	15/15	115/247	2.70	6.7	43	500	14	1200
24	1-A-224-15/15-77-7	7/32	0.224	5200	96	15/15	125/272	3.00	6.7	43	500	14	1200
25	1-A-224-15/15-35N-7	7/32	0.224	5200	100	15/15	125/272	2.40	6.7	43	500	14	1200
26	1-P-258-12/18-G-19	1/4	0.258	7000	122	12/18	282/282	1.90	4.0	50	300	14	1200
27	1-T-258-12/18-G-19	1/4	0.258	7000	125	12/18	282/282	1.90	4.0	56	500	14	1200
28	1-A-258-12/18-G-19	1/4	0.258	7000	126	12/18	282/282	1.90	4.0	52	550	14	1200
29	1-Q-258-12/18-G-19	1/4	0.258	7000	126	12/18	282/282	1.90	4.0	52	600	14	1200
30	1-A-258-12/18-75-19	1/4	0.258	6000	129	12/18	247/247	2.30	4.4	48	500	14	1200
31	1-A-258-12/18-77-19	1/4	0.258	6500	129	12/18	272/272	2.30	4.4	48	500	14	1200
32	1-A-258-12/18-35N-19	1/4	0.258	6500	135	12/18	272/272	1.40	4.4	48	500	14	1200
33	1-P-288-12/18-G-19	9/32	0.288	10000	154	12/18	370/370	1.60	2.8	57	300	16	1500
34	1-T-288-12/18-G-19	9/32	0.288	10000	159	12/18	370/370	1.60	2.8	64	500	16	1500
35	1-A-288-12/18-G-19	9/32	0.288	10000	159	12/18	370/370	1.60	2.8	54	550	16	1500
36	1-FT-288-12/18-G-19	9/32	0.288	10000	159	12/18	370/370	1.60	2.8	58	500	16	1500
37	1-Q-288-12/18-G-19	9/32	0.288	10000	159	12/18	370/370	1.60	2.8	54	600	16	1500
38	1-A-288-12/18-75-19	9/32	0.288	8200	159	12/18	308/308	1.90	4.0	54	500	16	1500
39	1-A-288-12/18-77-19	9/32	0.288	9200	158	12/18	335/335	1.90	4.0	54	500	16	1500
40	1-A-288-12/18-35N-19	9/32	0.288	9200	165	12/18	335/335	1.90	4.0	54	500	16	1500
41	1-P-322-12/18-G-19	5/16	0.322	11300	188	12/18	420/420	1.20	2.8	46	300	18	1500
42	1-FT-322-12/18-G-19	5/16	0.322	11300	195	12/18	420/420	1.20	2.8	45	500	18	1500
43	1-A-322-12/18-G-19	5/16	0.322	11300	196	12/18	420/420	1.20	2.8	45	550	18	1500
44	1-Q-322-12/18-G-19	5/16	0.322	11300	196	12/18	420/420	1.20	2.8	45	600	18	1500
45	1-FT-322-12/18-75-19	5/16	0.322	10400	197	12/18	387/387	1.20	3.3	45	500	18	1500
46	1-FT-322-12/18-77-19	5/16	0.322	11000	197	12/18	400/400	1.20	3.3	45	500	18	1500
47	1-FT-322-12/18-35N-19	5/16	0.322	11000	206	12/18	400/400	1.20	3.3	45	500	18	1500
48	1-P-380-12/18-G-19	3/8	0.380	15000	259	12/18	585/585	1.00	2.8	39	300	21	1500
49	1-FT-380-12/18-G-19	3/8	0.380	15000	269	12/18	585/585	1.00	2.8	39	500	21	1500
50	1-P-425-12/18-G-19	7/16	0.425	19500	320	12/18	726/726	0.70	2.8	34	300	24	1500
51	1-FT-425-12/18-G-19	7/16	0.425	19500	334	12/18	726/726	0.70	2.8	37	500	24	1500